

Printing date 30.03.2018

Version number 2

Revision and application 30.03.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: GALVA GRIS MAT

· Article number: 99660

- · Reference Safety data sheet Ref. 99660 EN FDS  $n^{\circ}622b$
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC11 Non industrial spraying
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GUILBERT EXPRESS

33, Avenue du Maréchal de Lattre de Tassigny

94127 FONTENAY SOUS BOIS Cedex

www.express-fds.fr

- · Further information obtainable from: info@express.fr
- · 1.4 Emergency telephone number:

+33/825 800 251

**ENGLAND** 

National Poisons Information Service:

- In England and Wales: NHS Direct 0845 4647;
- In Scotland: NHS 24 08454 24 24 24

*IRELAND* 

National Poisons Information Centre, 01 8092566 or 01 8379964.

## SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Version number 2 Revision and application 30.03.2018 Printing date 30.03.2018

Trade name: GALVA GRIS MAT

(Contd. of page 1)

#### · Hazard pictograms







GHS02

GHS07

· Signal word Danger

## · Hazard-determining components of labelling:

*Hydrocarbures, C6, isoalcanes, <5% n-hexane* Solvent naphtha (petroleum), light arom.

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Causes serious eye irritation. H319

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	10-25%
EINECS: 203-603-9	♦ Flam. Liq. 3, H226	
CAS: 67-64-1	acetone	10-25%
EINECS: 200-662-2	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3,	
Reg.nr.: 01-2119471330-49-XXXX	H336	
EC number: 931-254-9	Hydrocarbures, C6, isoalcanes, <5% n-hexane	2.5-10%
	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	
CAS: 1330-20-7	Xylol, Isomerengemisch (wenn Flammpunkt<21°C)	2.5-10%
	♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

(Contd. on page 3)

Printing date 30.03.2018 Version number 2 Revision and application 30.03.2018

Trade name: GALVA GRIS MAT

	(Con	td. of page 2)
CAS: 78-93-3	butanone	2.5-10%
EINECS: 201-159-0	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 95-63-6	1,2,4-trimethylbenzene	<i>≤</i> 2.5%
EINECS: 202-436-9	♠ Flam. Liq. 3, H226; ♠ Aquatic Chronic 2, H411; ♠ Acut Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	e
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom.  Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H335	≤2.5%

#### · Additional information:

EINECS: 931-254-9

Identification: HYDROCARBONS, C6, ISOALCANES, <5% N-HEXANE

Concentration: 5 < x % < 10

Classifcation:

GHS09, GHS07, GHS08, GHS02, Attention

H:225-304-336-411

EUH:066 Xn,N,F

R: 11-65-67-51/53

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.

(Contd. on page 4)

Version number 2 Revision and application 30.03.2018 Printing date 30.03.2018

Trade name: GALVA GRIS MAT

(Contd. of page 3)

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: Storage temperature: Room temperature
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

	Ingredients with	limit values t	hat require	monitoring at ti	he workplace:
--	------------------	----------------	-------------	------------------	---------------

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

## 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

#### 1330-20-7 Xylol, Isomerengemisch (wenn Flammpunkt<21°C)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm Sk. BMGV

#### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

## 95-63-6 1,2,4-trimethylbenzene

WEL Long-term value: 125 mg/m³, 25 ppm

## Ingredients with biological limit values:

#### 1330-20-7 Xylol, Isomerengemisch (wenn Flammpunkt<21°C)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

(Contd. on page 5)

Version number 2 Revision and application 30.03.2018 Printing date 30.03.2018

Trade name: GALVA GRIS MAT

(Contd. of page 4)

#### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses

Tightly sealed goggles

· **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Compressed liquefied gas Form:

Colour: Dark grey · Odour: Characteristic

· pH-value: Not determined.

· Change in condition

*Melting point/freezing point:* Not determined.

Initial boiling point and boiling range: 36 °C

(Contd. on page 6)

Printing date 30.03.2018 Version number 2 Revision and application 30.03.2018

Trade name: GALVA GRIS MAT

	(Contd.	of page
Flash point:	-19 °C	
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	315 °C	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	1.5 Vol %	
Upper:	13.0 Vol %	
Vapour pressure at 20 °C:	233 hPa	
Density at 20 °C:	0.96 g/cm³	
Solubility in / Miscibility with		
water:	Soluble.	
Solvent content:		
VOC (EC)	40.00 %	
9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Avoid temperatures above 50°C
- · 10.5 Incompatible materials:

Oxidizing materials

Strong Acids

Alkali

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

GB

Printing date 30.03.2018 Version number 2 Revision and application 30.03.2018

Trade name: GALVA GRIS MAT

(Contd. of page 6)

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN1950	
1950 AEROSOLS	
AEROSOLS	
AEROSOLS, flammable	
2 5F Gases.	
2.1	
2.1	
2.1	

Printing date 30.03.2018 Version number 2 Revision and application 30.03.2018

Trade name: GALVA GRIS MAT

	(Contd. of page
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abov
	1 litre: Category B. For WASTE AEROSOLS: Category
	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre: Segregation as for class 9. Stow "separated from
	class 1 except for division 1.4. For AEROSOLS with
	capacity above 1 litre: Segregation as for the appropria
	subdivision of class 2. For WASTE AEROSOLS
	Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to Ann	ex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

(Contd. on page 9)

Printing date 30.03.2018

Version number 2

Revision and application 30.03.2018

Trade name: GALVA GRIS MAT

(Contd. of page 8)

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols - Category 1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.