



Product Technical Data

GUILBERT EXPRESS

Le Périgole, Lot 209-210

33 avenue du Maréchal de Lattre de Tassigny

94127 Fontenay sous Bois Cedex - France

Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Stand-alone soldering iron type 364	
Created on	23/01/2006
Modified on	16/09/2014
Issue	J

Ref.: 6364 - 364
Name: Soldering iron

**This equipment must be used
with gas cartridges
Ref. 444 and 445 only**

Product: Roofing soldering iron
Activity: Roofing
User: Professional
Energy: Gas

Description

Stand-alone, hoseless handle + roofing burner.
Compact and light-weight.
Cercoflam type enveloping flame.
Low noise level.
Heating time twice shorter than that of a conventional iron.
Significant energy saving.
0 to 360° swivelling bit, with $\pm 5^\circ$ tilting angle for improved handling.
Semisteel body with anticorrosion protection treatment.
Burners suitable for work on zinc, copper, stainless steel, pre-patinated zinc, lead, etc.
Spring effect, 2-position stand.

Application field

Roofing, sheet metal working, etc.



Technical features

At 2 bar	Flow in g/h	Power		Max. temperature	
		In kW	In BTU	In °C	In °F
All references type 367	94 g/h	1.3 kW	4400	600°C	1110°F

Spare parts

Iron bits See iron bit technical data sheet
Injectors, x5 Ref. 36713

Standard composition

Ref.	Description	Weight (bare)	Dimensions
364	Soldering iron + "turbo" bit Ref. 778 + 1 gas cartridge Ref. 444	1230 g	-
6364	Soldering iron + "turbo" bit Ref. 778 + 2 gas cartridges Ref. 444 + 1 empty bottle for flux (capacity 100 ml) + 1 spare injector	3300 g	365 x 180 x 80 mm
4367/8	Roofing burner + bit Ref. 678	520 g	-

Materials

Iron bit: Copper, 99.9% pure
Burner: Semisteel, with anticorrosion treatment
Venturi: Stainless steel
Valves and fittings: Brass

IMPORTANT: Read instructions before use - Use only in well ventilated areas.

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Actual products may differ from photographs.

www.guilbert-express.net