

GUILBERT EXPRESS

Le Pérípole - Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex - France
Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Torches - 510X - 520X	
Created on	07/03/11
Modified on	22/12/11
Issue	B

Ref.:	5100 - 5200
Name:	Standard gas torch

Product:	Gas torch
Activities:	Plumbing / Odd-job
User:	General public
Energy:	Butane

Application fields:

Plumbing, odd-job, heating, deburring, de-icing



Description - Ref. 5100

Butane gas torch
Rubber hose, 1.50 m long, ISO 3821
Butane cylinder connection: Depending on country
1 sharp tip flame: Length 70 mm

Description - Ref. 5200

Butane gas torch
Rubber hose, 1.50 m long, ISO 3821
Butane cylinder connection: Depending on country
1 sharp tip flame: Length 70mm
1 Cercoflam: Enveloping flame
1 paint burner: Flat flame

Technical features

Butane gas flow (g/h) at 1.5 bar	310 g/h	
Power	4.3 kW	14,700 BTU
Flame temperature	1850 °C	3300 °F

Soldering capacity on copper tube

	Sharp tip flame	Cercoflam
Max. diameter of copper tube with CuPh solder	Dia. 18 mm	Dia. 24 mm

Spare parts

Paint burner	Ref. 4716
Cercoflam	Ref. 7693



Packaging

	Weight (g)	Width (mm)	Depth (mm)	Height (mm)
Cardboard box, 4x5100	2435	430	327	105
Cardboard box, 4x5200	2860	430	327	105

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Non-contractual photos.

www.guilbert-express.net