

Product Technical Data

GUILBERT EXPRESS

10 rue Henry Delbast

77183 Croissy-Beaubourg

Tél : 0.825.800.251 - Fax : 0.825.800.238

Burners - Flat serie - 1660 - 1662

Created on	16/07/2003
Modified on	23/10/2024
Issue	E

Ref.: 1660
1662
Name: Burners - Flat serie

Product: Burner
Activity: Roofing
User: Professionals - General public - DIY
Energy: PROPANE GAS

Description

Rear air inlet nozzle (primary suction), producing excellent flame in any position, especially when directed towards the ground.

Application fields: burning, roofing, disinfection.

Gas supply from 2 to 4 bar

Stainless steel nozzle.



	1660	1662
Gas reference	Propane	Propane
Pressure	4b / 58 psi	4b / 58 psi
Gas flow	4400 g/h	10800 g/h
Power kW	60	150
BTU/h	208000	511000

Spare parts	1660	1662
Gas outlet Ref.	4629	4824

Accessory	Reference	Length
Extension	4726	40 cm
Extension	4727	20 cm

Miscellaneous	1660	1662
Nozzle cross-section (mm)	100 x 35	168 x 48
Flame length (mm) (3 bar)	310	600



Packaging	1660	1662
Weight (g)	400	620
Type	Burner hook	

Regulation**Designed as per: EN731****Burners to be used with EXPRESS handles only.****IMPORTANT: Read instructions before use - Use only in well ventilated areas.**

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice.

Actual products may differ from photographs.

www.guilbert-express.net