

Cat. No. : 2015

Description : Gas cartridge

Type :

Professional, for use with :

- Cartridge blowtorches Cat. No. 351 / 343 / 525
- Oxy-gas sets Cat. No. 2901 / 2902 / G2903

Applications :

Plumbing, tin soldering, unjamming, burning.

Includes the following :

- LPG + pentane mixture
- Net gas mass : 326 g / 600 ml
- 22,5-bar steel casing (recyclable)

European standard screw valve :

- 7/16" – 28 threads per inch (60 °C – 140 °F)

Use in all seasons :

- Down to -13 °C (8.6 °F) with a new cartridge

Unit weight and dimensions :

- Weight: 460 g
- Diameter: 66 mm
- Height: 278 mm

Box weight and dimensions :

Box of 12 cartridges

- Weight: 5,7 kg
- Width: 265 mm
- Depth: 205 mm
- Height: 290 mm

Recommendations :

- Single-use, non-rechargeable cartridge.
- Keep away from sunlight
- Do not expose to temperatures exceeding 50°C (122°F)
- Store in a dry, well-ventilated room

Picture :



Safety Data Sheet (SDS) :

SDS N° 007

Compliance :

NF EN 417

Barcode

3 18964002015 3

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs.

www.express.fr

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tel: 0.825.800.251 - Fax: 0.825.800.238