

Product Technical Data

GUILBERT EXPRESS

Le Pérípole, Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
F - 94127 Fontenay sous Bois Cedex - France
Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Roofing soldering iron type 467	
Created on	12/04/2010
Modified on	16/04/2016
Issue	F

Cat. No. 6178 - 6179 - 60278 -
60279 - 6678 - 6679 -
66278 - 66279 - 4675 -
4678 - 4679 - 66378 -
66379
Name: Soldering iron

Product: Roofing soldering iron
Activity: Roofing
User: Professional
Energy: Gas

Description

Compact and light-weight.
Cercoflam type enveloping flame.
Low noise level.
Heating time twice shorter than that of a conventional iron.
Significant energy saving.
0 to 360° swivelling bit, with ±5° tilting angle for improved handling.
Semisteel body with anticorrosion treatment.
Burners suitable for work on zinc, copper, stainless steel, pre-patinated zinc, lead, etc.
Spring effect, 2-position stand.
Supply pressure: 2 bar

Application field

Roofing, sheet metal working, etc.



Technical features

At 2 bar	Flow g/h	Power		Max. temperature	
		kW	BTU	°C	°F
All references type 367	94 g/h	1.3 kW	4400	600 °C	1110 °F

Spare parts

Iron bits See iron bit technical data sheet
Injectors, x 5 Cat. No. 36714

Standard composition

Cat. No.	Description			Weight (bare)
	Hose	Handle	Burner	
4675	NO	NO	Burner + bit 675	490 g
4678	NO	NO	Burner + bit 678	540 g
4679	NO	NO	Burner + bit 679	610 g
6178	NO	Handle with fixed 3/8"G union Cat. No. 600	Burner 4678	855 g
6179	NO		Burner 4679	925 g
60278	NO	Handle with 3/8"G swivelling union Cat. No. 602	Burner 4678	865 g
60279	NO		Burner 4679	935 g
63778	NO	3/8" swivelling + bent nipple (45°) and quick -release coupling 3/8" Cat. No. 603CR	Burner + bit 778	985g
63779	NO		Burner + bit 779	1050g
6678	Regulator 2 bar Cat. No. 682 + hose 4.75 m long Cat. No. 963/5	Handle with fixed 3/8"G union Cat. No. 600	Burner 4678	1415 g
6679			Burner 4679	1485 g
66278		Handle with 3/8"G swivelling union Cat. No. 602	Burner 4678	1425 g
66279			Burner 4679	1495 g
66378		3/8" swivelling + bent nipple (45°) and quick -release coupling 3/8" Cat. No. 603CR	Burner + bit 778	1450g
66379			Burner + bit 779	1545g

Materials

Iron bit: Copper, 99.9% pure
Burner: Semisteel, anticorrosion treatment
Venturi: Stainless steel
Valves and fittings: Brass

Designed as per NF EN 731

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without previous notice.

Actual products may differ from photographs.

www.guilbert-express.net