

**GUILBERT EXPRESS** 

Product Technical Data

Burners - Flat serie - 1660 - 1662			
Created on	16/07/03		
Modified on	23/04/13		
Issue	С		

Le Péripole - Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex - France
Tel.: + 33 1 53 99 16 98 - Fax : + 33 1 53 99 16 56

Defi	1660	Product:	Burner
Ref.:	1662	Activity:	Roofing
Neme	Name: Burners - Flat serie	User:	Professionals - General public - DIY
Name:		Energy:	PROPANE GAS

## Description

Rear air inlet nozzle (primary suction), producing excellent flame in any position, especially when directed towards the ground.

Application fields: burning, roofing, disinfection. Gas supply from 2 to 4 bar

Stainless steel nozzle.





[	1660	1662		
Gas reference	Propane	Propane		
Pressure	4b / 58 psi	4b / 58 psi		
Gas flow	2898	11777		
Power kW	40	163		
BTU/h	136500	55500		
-				
Spare parts	1660	1662		
Gas outlet Ref.	4629	4824		
Accessory	Reference	Length		
Extension	4726	40 cm		
Extension [	4727	20 cm		
Miscellaneous	1660	1662		
Nozzle cross-section (mm)	100 × 35	168 × 48		
Flame length (mm) (3 bar)	310	600		



## Regulation

Designed as per: EN731

Burners to be used with EXPRESS handles only.

IMPORTANT: Read instructions before use - Use only in well ventilated areas.

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice.

Actual products may differ from photographs. www.guilbert-express.net