

Product datasheet

GUILBERT EXPRESS
Le Pérépole, Lot 209-210
33 avenue du Maréchal de Lattre de Tassigny
94127 Fontenay sous Bois Cedex
Tel: +33 (0)825 800 251 - Fax: +33 (0)825 800 238

Cat. No.: 460	
Created on:	08/06/2020
Modified on:	08/06/2020
Issue:	A

Description

Piezo ignition
Flow rate controlled by regulator
Can be pointed downward instantly
Hanging ring
Accurate gas flow control
Removable stabilizer stand
Attractive plastic casing
Handle with safety cut-off
MAPP and propane gas compatible
Continuous or trigger-controlled flame

Areas of application

Plumbing, welding, brazing, flame cleaning, unjamming, burning, defrosting.

Vulcane ONE weight: 375 g
Weight in packaging on hang tab: 450 g



Technical data

Gas	Pressure		Consumption	Power		For tube	"Turbo" type flame		
	Type	bar		psi	g/h		kW	BTU/h	Cu Ø (mm)
XPRESS 2400		1.4	20	204	2.7	9200	10 - 22	18	80
Propane		1.4	20	227	3.1	10690	10 - 22	18	80

Spare parts

Designation	Cat. No.
100% propylene cylinder	2400
Stabiliser stand	4702
Extension hose	4770

2400



4770

4702



IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs

www.guilbert-express.net